



# NTN BEARING CORP.OF AMERICA



5222C3 Bearing 2D drawings and 3D CAD models

4.331 Inch | 110 Millimeter x 7.874 Inch | 200 Millimeter x 2.748 Inch | 69.8 Millimeter Timken 5222C3 Angular Contact Bearings

Bearing No. 5222C3

|                                 |   |
|---------------------------------|---|
| Category                        | Angular Contact Ball Bearings   |
| Inventory                       | 0.0   |
| Manufacturer Name               | TIMKEN  |
| Minimum Buy Quantity            | N/A   |
| Weight                          | 9.511   |
| EAN                             | 0087796068025   |
| Product Group                   | B00152  |
| Enclosure                       | Open  |
| Flush Ground                    | No  |
| Rolling Element                 | Ball Bearing  |
| Number of Rows of Balls         | Double Row  |
| Precision Class                 | ABEC 1   ISO P0   |
| Maximum Capacity / Filling Slot | No  |
| Snap Ring                       | No  |
| Cage Material                   | Steel   |
| Contact Angle                   | 30 Degree   |
| Internal Clearance              | C3-Loose  |
| Number of Bearings              | 1 (Single)  |
| Inch - Metric                   | Metric  |
| Long Description                | 110MM Bore; 200MM Outside Diameter; 69.8MM Width; Open; No Flush Ground; Ball Bearing; Double Row of Balls; ABEC 1   ISO P0; No Filling Slot; |



## NTN BEARING CORP.OF AMERICA

|                          |   |
|--------------------------|---|
|                          | No Snap Ring; C3-Loose;<br>Steel Cage; 30 Degree; 1<br>(Single) |
| Category                 | Angular Contact Ball<br>Bearing                                 |
| UNSPSC                   | 31171531  |
| Harmonized Tariff Code   | 8482.10.50.28   |
| Noun                     | Bearing   |
| Keyword String           | Angular Contact   |
| Manufacturer URL         | <a href="http://www.timken.com">http://www.timken.com</a>       |
| Manufacturer Item Number | 5222C3  |
| Weight / LBS             | 20.95   |
| D                        | 7.874 Inch   200 Millimeter                                     |
| B                        | 2.748 Inch   69.8 Millimeter                                    |
| d                        | 4.331 Inch   110 Millimeter                                     |